

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14219AD54
Minimum Qty (MOQ):	130 EA
NSN:	5320-01-467-8633
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14219AD5-4 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.014 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/chamfered Tip
Head Major Diameter:	0.210 Inches Nominal
End Item Identification:	C17a Aircraft
Grip Length:	0.178 Inches Nominal
Minimum Tensile Strength:	38000 Pounds Per Square Inch
Minimum Yield Strength:	18000 Pounds Per Square Inch
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	120.0 Degrees Nominal
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Ms14219 Mil Std All Material Responses Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,typeii,class1 Mil Std All Treatment Responses Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219AD5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.