

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS14219AD55 |
| Minimum Qty (MOQ): | 50 EA |
| NSN: | 5320-01-467-8630 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14219AD5-5 Specifications

| | |
|---|--|
| Fastener Length: | 0.3125 Inches Nominal |
| Head Style: | Countersunk W/ Reverse Chamfer |
| Head Height: | 0.021 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight W/chamfered Tip |
| Head Major Diameter: | 0.258 Inches Nominal |
| End Item Identification: | C17a Aircraft |
| Grip Length: | 0.2205 Inches Nominal |
| Minimum Tensile Strength: | 38000 Pounds Per Square Inch |
| Minimum Yield Strength: | 18000 Pounds Per Square Inch |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 120.0 Degrees Nominal |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Ms14219 Mil Std All Material Responses Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,typeii,class1 Mil Std All Treatment Responses Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219AD5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.