

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS14219E47       |
| Minimum Qty (MOQ): | 250 EA           |
| NSN:               | 5320-01-390-7092 |
| Schedule B:        | 7616.10.3000     |
| ECCN:              | 9A991            |



NO IMAGE  
AVAILABLE

## P/N MS14219E4-7 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| <b>Head Style:</b>                           | Dished Countersunk                                 |
| <b>Shank Diameter:</b>                       | 0.124 Inches Minimum And 0.127 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight W/chamfered Tip                           |
| <b>Head Major Diameter:</b>                  | 0.208 Inches Minimum And 0.210 Inches Maximum      |
| <b>Minimum Tensile Strength:</b>             | 68000 Pounds Per Square Inch                       |
| <b>Minimum Yield Strength:</b>               | 58000 Pounds Per Square Inch                       |
| <b>Shear Strength:</b>                       | 46000 Single Pounds Per Square Inch                |
| <b>Countersink Angle:</b>                    | 118.5 Degrees Minimum And 121.5 Degrees Maximum    |
| <b>Material:</b>                             | Aluminum Alloy 7075 Overall                        |
| <b>Material Document And Classification:</b> | Qq-q-430 Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                    | Anodize Overall                                    |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219E4-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.