

Description

Fastener Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14219E516
Minimum Qty (MOQ):	80 EA
NSN:	5320-01-391-2195
Schedule B:	7616.10.3000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS14219E5-16 Specifications

<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Dished Countersunk
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/chamfered Tip
<b>Head Major Diameter:</b>	0.256 Inches Minimum And 0.258 Inches Maximum
<b>Minimum Tensile Strength:</b>	68000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	58000 Pounds Per Square Inch
<b>Shear Strength:</b>	46000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	118.5 Degrees Minimum And 121.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-q-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219E5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.