

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS14219E57 |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5320-01-391-2199 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N MS14219E5-7 Specifications

| | |
|--|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Dished Countersunk |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight W/chamfered Tip |
| Head Major Diameter: | 0.256 Inches Minimum And 0.258 Inches Maximum |
| Minimum Tensile Strength: | 68000 Pounds Per Square Inch |
| Minimum Yield Strength: | 58000 Pounds Per Square Inch |
| Shear Strength: | 46000 Single Pounds Per Square Inch |
| Countersink Angle: | 118.5 Degrees Minimum And 121.5 Degrees Maximum |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219E5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.