

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14219E68
Minimum Qty (MOQ):	145 EA
NSN:	5320-01-390-7104
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N MS14219E6-8 Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Dished Countersunk
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight W/chamfered Tip
Head Major Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Minimum Tensile Strength:	68000 Pounds Per Square Inch
Minimum Yield Strength:	58000 Pounds Per Square Inch
Shear Strength:	46000 Single Pounds Per Square Inch
Countersink Angle:	118.5 Degrees Minimum And 121.5 Degrees Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS14219E6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.