

**Description**

MS14222-3 Self-Locking Extended Washer Nut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS142223
Minimum Qty (MOQ):	10
NSN:	5310-01-304-7971
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS14222-3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.330 Inches Maximum
<b>Counterbore Diameter:</b>	0.190 Inches Minimum Washer And 0.220 Inches Maximum Washer
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Height:</b>	0.154 Inches Minimum And 0.188 Inches Maximum
<b>Nut Style:</b>	Hexagon
<b>Washer Thickness:</b>	0.015 Inches Minimum
<b>Nut Counterbore Depth:</b>	0.006 Inches Minimum Washer And 0.031 Inches Maximum Washer
<b>Width Across Flats:</b>	0.243 Inches Minimum And 0.252 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/MS14222-3](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14222-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.