

Description

MS14222-3 Self-Locking Extended Washer Nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS142223
Minimum Qty (MOQ):	10
NSN:	5310-01-304-7971
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14222-3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.330 Inches Maximum
Counterbore Diameter:	0.190 Inches Minimum Washer And 0.220 Inches Maximum Washer
Lubrication:	Dry Film Lubricant
Overall Height:	0.154 Inches Minimum And 0.188 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.015 Inches Minimum
Nut Counterbore Depth:	0.006 Inches Minimum Washer And 0.031 Inches Maximum Washer
Width Across Flats:	0.243 Inches Minimum And 0.252 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14222-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.