



Military-Fasteners.com

P/N MS14226-32KD10

Description

Hole Diameter: 1/4", Diameter: 1/2", Thickness: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1422632KD10
Minimum Qty (MOQ):	250 EA
NSN:	5310-01-434-2974
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14226-32KD10 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.231 Inches Minimum And 0.236 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	0.433 Inches Minimum And 0.458 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5 T3 Fed Spec Single Material Response Overall Or Qq-a-250/5, T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14226-32KD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.