

P/N MS14226-64KD616

Description

Hole Diameter: 3/8", Diameter: 5/8", Thickness: 1/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS1422664KD616

Minimum Qty (MOQ): 115 EA

NSN: 5310-01-434-3334

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS14226-64KD616 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.400 Inches Minimum And 0.405 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	0.620 Inches Minimum And 0.645 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5, T3 Fed Spec Single Material Response Overall Or Qq-a-250/5, T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/MS14226-64KD616 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.