

## P/N MS14226-64KD616

### **Description**

Hole Diameter: 3/8", Diameter: 5/8", Thickness: 1/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS1422664KD616

Minimum Qty (MOQ): 115 EA

NSN: 5310-01-434-3334

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS14226-64KD616 Specifications

| Cross-sectional Shape Style:                          | Rectangular  |
|---|--|
| Hole Diameter:  | 0.400 Inches Minimum And 0.405 Inches Maximum  |
| Peripheral Shape Style:                               | Round  |
| Center Hole Shape Style:                              | 1 Round  |
| Thickness:  | 0.057 Inches Minimum And 0.069 Inches Maximum  |
| Overall Diameter:                                     | 0.620 Inches Minimum And 0.645 Inches Maximum  |
| Material:   | Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall  |
| Material Document And Classification:                 | Qq-a-250/5, T3 Fed Spec Single Material Response Overall Or Qq-a-250/5, T4 Fed Spec Single Material Response Overall |
| Surface Treatment:                                    | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall  |

## **How to Order**

Order this washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/MS14226-64KD616">https://military-fasteners.com/washers/flat+washers/MS14226-64KD616</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.