

Description

thread: 1/4-28, tapered, straight fitting, lubrication hydraulic surface check, steel, 1680-AS, MS15001 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1680-AS](#) [AS15001-2P](#)

| | |
|-------------------------|---|
| SKU / Model: | MS150012 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 4730-00-172-0001 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N MS15001-2 Specifications

| | |
|--|---|
| Shank Length: | 0.625 Inches Nominal |
| Screw Thread Series Designator: | Sae-It |
| Width Across Flats: | 0.312 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Special Features: | Supports Harnischfeger Corp.;model M320t2,crane Truck Mounted,nsn 3810-00-151-4431 And Surface Located Ball Check Valve |
| Height: | 0.937 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Zinc Overall |
| Style Designator: | Straight |

How to Order

Order this lubrication fitting from our inventory online by visiting <https://military-fasteners.com/fittings/lubrication+fittings/MS15001-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.