

# P/N MS15002-3

Military-Fasteners.com

#### Description

thread: 1/4-28, straight, lubrication hydraulic surface check, steel, MS15002 series fitting

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS150023
Minimum Qty (MOQ):	10
NSN:	4730-00-172-0015
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS15002-3 Specifications

Shank Length:	0.125 Inches Nominal
Angle In Deg:	45.0
Screw Thread Series Designator:	Sae-It
Assembly Clearance Radius:	0.438 Inches Maximum
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Special Features:	Surface Located Ball Check Valve, used On Grumman A-10 Aircraft
Height:	0.750 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Surface Treatment:	Cadmium Or Zinc Overall
Style Designator:	Angle
Specification/standard Data:	96906-ms15002 Government Standard

### How to Order

Order this lubrication fitting from our inventory online by visiting <u>https://military-fasteners.com/fittings/lubrication+fittings/MS15002-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.