

P/N MS15795-802B

Description

Hole Diameter: 3/32", Diameter: 1/4", Thickness: 1/64", black oxide film, MS15795 series washer

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS15795802B

Minimum Qty (MOQ): 100

NSN: 5310-00-433-3599

Schedule B: 7318.22.0000

ECCN: 9A991

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc









^{*} See page 2 for technical characteristics

P/N MS15795-802B Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.089 Inches Minimum And 0.094 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.016 Inches Minimum And 0.025 Inches Maximum
Overall Diameter:	0.245 Inches Minimum And 0.250 Inches Maximum
Color:	Black Overall
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Oxide Film Overall
Surface Treatment Document And Classification:	Mil-c-13924,class 4 Mil Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	A Type And 1 Grade And B Class

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/MS15795-802B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS15795-802B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS15795-802B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/ms15795-802B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/ms15795-802B and selecting the property of the pro