

# P/N MS15795-858B

# **Description**

Hole Diameter: 17/64", Diameter: 29/64", Thickness: 1/32", black oxide

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS15795858B

Minimum Qty (MOQ): 100

NSN: 5310-01-419-1835

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS15795-858B Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.256 Inches Minimum And 0.266 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.046 Inches Maximum
Overall Diameter:	0.438 Inches Minimum And 0.468 Inches Maximum
Color:	Black Overall
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Oxide Overall

# **How to Order**

Order this flat washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/MS15795-858B">https://military-fasteners.com/washers/flat+washers/MS15795-858B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/flat+washers/MS15795-858B">https://military-fasteners.com/washers/flat+washers/MS15795-858B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/flat+washers/MS15795-858B">https://military-fasteners.com/washers/flat+washers/MS15795-858B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/ms15795-858B">https://military-fasteners.com/washers/ms15795-858B</a> and selecting the quantity you want <a href="https://military-fasteners.com/washers/ms15795-858B">https://military-fasteners.com/washers/ms15795-858B</a> and selecting the property of t