

Description

Fastener Length: 27/32", Thread: 3/8-16, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1620549
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-177-5655
Schedule B:	7415.39.0000
ECCN:	9A991
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc



* See page 2 for technical characteristics

P/N MS16205-49 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.719 Inches Minimum And 0.906 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.906 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.544 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:	Copper Alloy 651 Overall
Material Document And Classification:	Qq-c-591 Fed Spec Single Material Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS16205-49> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.