



★ FASTENERS

Military-Fasteners.com

P/N MS16228-4C

Description

Thread Size: 1/4", Nut Height: 1/4", Head Width: 1/2", MS16228 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS162284C
Minimum Qty (MOQ):	10
NSN:	5310-00-245-8825
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N MS16228-4C Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Hexagon
Nut Height:	0.266 Inches Minimum And 0.296 Inches Maximum
End Item Identification:	5895-01-514-7015, Communications Interface System (cis) (v) 2; Rg-33 Mrap
Width Across Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.250 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Part Name Assigned By Controlling Agency:	Nut, Self-locking, Hexagon - Thin, Unc 3b (non-metallic Insert) Austenitic Corrosion Resistant Steel, Nonmagnetic, 250 Deg Fahr
Material:	Plastic Polyhexamethylene Amide Locking Insert
Material:	Steel Overall Except Insert
Material Document And Classification:	66 Fed Std All Material Responses Overall Except Insert
Material Document And Classification:	Mil-m-20693,comp A,ty 1 Mil Spec Single Material Response Locking Insert
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Specification/standard Data:	80205 - Nas-16228. Sep 1999 Professional/Industrial Association Specification

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS16228-4C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.