

Description

MS16555-22 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS1655522 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5315-00-894-2566 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS16555-22 Specifications

| | |
|--|---|
| First End Style: | Chamfered |
| Second End Style: | Square |
| Pin Overall Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Pin Overall Diameter: | 0.0939 Inches Minimum And 0.0941 Inches Maximum |
| First End Taper Length: | 0.157 Inches Maximum |
| Features Provided: | Casehardened |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 47.0 Rockwell C Minimum Overall And 58.0 Rockwell C Maximum Overall |
| Shear Strength: | 1800 Double Pound |
| First End Taper Angle: | 4.0 Degrees Minimum And 16.0 Degrees Maximum |
| Surface Finish: | 16.0 Microinches Outside Diameter |
| Material: | Steel Overall |
| Material Document And Classification: | Astm A29 Assn Std Single Material Response Overall |

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.