

Description


MS16555-27 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1655527
Minimum Qty (MOQ):	50
NSN:	5315-00-822-1180
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16555-27 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Pin Overall Diameter:	0.1251 Inches Minimum And 0.1253 Inches Maximum
Second End Corner Radius:	0.041 Inches Maximum
First End Taper Length:	0.084 Inches Maximum
Features Provided:	Casehardened
Second End Relationship With First End:	Not Identical
Hardness Rating:	47.0 Rockwell C Minimum Overall And 58.0 Rockwell C Maximum Overall
Shear Strength:	3200 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Radius End May Be Chamfered 25.0 Degrees
Material:	Steel Overall
Material Document And Classification:	Astm A29 Assn Std Single Material Response Overall

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.