

Description

MS16555-40, Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS1655540 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5315-00-811-6495 |
| ECCN: | EAR99 |
| National Motor Freight: | 105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes |



* See page 2 for technical characteristics

P/N MS16555-40 Specifications

| | |
|--|---|
| First End Style: | Chamfered |
| Second End Style: | Radius |
| Pin Overall Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Pin Overall Diameter: | 0.1876 Inches Minimum And 0.1878 Inches Maximum |
| Second End Corner Radius: | 0.062 Inches Maximum |
| First End Taper Length: | 0.114 Inches Nominal |
| Features Provided: | Casehardened |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 58.0 Rockwell C Minimum Overall And 64.0 Rockwell C Maximum Overall |
| Shear Strength: | 7200 Double Pound |
| First End Taper Angle: | 4.0 Degrees Minimum And 16.0 Degrees Maximum |
| Surface Finish: | 16.0 Microinches Outside Diameter |
| Special Features: | Radius End May Be Chamfered 25.0 Degrees |
| Material: | Steel Overall |
| Material Document And Classification: | Astm A29 Assn Std Single Material Response Overall |

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.