

# P/N MS16555-53

## **Description**

MS16555-53 Straight Headless Pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS1655553

Minimum Qty (MOQ): 10

NSN: 5315-00-927-7893

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16555-53 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Pin Overall Diameter:	0.3126 Inches Minimum And 0.3128 Inches Maximum
Second End Corner Radius:	0.039 Inches Minimum And 0.104 Inches Maximum
First End Taper Length:	0.178 Inches Nominal
Features Provided:	Casehardened
Second End Relationship With First End:	Not Identical
Hardness Rating:	47.0 Rockwell C Minimum Overall And 58.0 Rockwell C Maximum Overall
Shear Strength:	20000 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Radius End May Be Chamfered 25 Degrees
Material:	Steel Overall
Material Document And Classification:	Astm A29 Assn Std Single Material Response Overall

### **How to Order**

Order this straight headless pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/straight+headless+pins/MS16555-53">https://military-fasteners.com/pins/straight+headless+pins/MS16555-53</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.