

Description

MS16555-60 Straight Headless Pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1655560
Minimum Qty (MOQ):	50
NSN:	5315-00-820-8051
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS16555-60 Specifications

<b>First End Style:</b>	Chamfered
<b>Second End Style:</b>	Radius
<b>Pin Overall Length:</b>	1.240 Inches Minimum And 1.260 Inches Maximum
<b>Pin Overall Diameter:</b>	0.3751 Inches Minimum And 0.3753 Inches Maximum
<b>Second End Corner Radius:</b>	0.047 Inches Minimum And 0.125 Inches Maximum
<b>First End Taper Length:</b>	0.101 Inches Nominal
<b>Features Provided:</b>	Casehardened
<b>Second End Relationship With First End:</b>	Not Identical
<b>Hardness Rating:</b>	47.0 Rockwell C Minimum Overall And 58.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	28000 Double Pound
<b>First End Taper Angle:</b>	4.0 Degrees Minimum And 16.0 Degrees Maximum
<b>Special Features:</b>	Radius End May Be Chamfered 25.0 Degrees
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Astm A29 Assn Std Single Material Response Overall

## How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.