

P/N MS16555-606

Description

MS16555-606 Straight Headless Pin

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS16555606

Minimum Qty (MOQ): 100

NSN: 5315-00-841-5416

ECCN: EAR99

National Motor Freight: 105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes



^{*} See page 2 for technical characteristics

P/N MS16555-606 Specifications

First End Style:	Chamfered
Second End Style:	Square
Pin Overall Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Pin Overall Diameter:	0.0626 Inches Minimum And 0.0628 Inches Maximum
First End Taper Length:	0.109 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	610 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this straight headless pin from our inventory online by visiting https://military-fasteners.com/pins/straight+headless+pins/MS16555-606 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/straight+headless+pins/MS16555-606 and selecting the