

**Description**

MS16555-607 Straight Headless Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16555607
Minimum Qty (MOQ):	100
NSN:	5315-00-807-7956
ECCN:	EAR99
National Motor Freight:	105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes



NO IMAGE  
AVAILABLE

## P/N MS16555-607 Specifications

<b>First End Style:</b>	Chamfered
<b>Second End Style:</b>	Square
<b>Pin Overall Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Pin Overall Diameter:</b>	0.0626 Inches Minimum And 0.0628 Inches Maximum
<b>First End Taper Length:</b>	0.142 Inches Nominal
<b>Features Provided:</b>	Casehardened
<b>Second End Relationship With First End:</b>	Not Identical
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	610 Double Pound
<b>First End Taper Angle:</b>	4.0 Degrees Minimum And 16.0 Degrees Maximum
<b>Surface Finish:</b>	16.0 Microinches Outside Diameter
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 416 Overall
<b>Material Document And Classification:</b>	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Astm A380 Assn Std Single Treatment Response Overall

## How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-607> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.