

Description

MS16555-608 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS16555608 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5315-00-807-7957 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N MS16555-608 Specifications

| | |
|---|--|
| First End Style: | Chamfered |
| Second End Style: | Square |
| Pin Overall Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Pin Overall Diameter: | 0.0626 Inches Minimum And 0.0628 Inches Maximum |
| First End Taper Length: | 0.173 Inches Nominal |
| Features Provided: | Casehardened |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| Shear Strength: | 610 Double Pound |
| First End Taper Angle: | 4.0 Degrees Minimum And 16.0 Degrees Maximum |
| Surface Finish: | 16.0 Microinches Outside Diameter |
| Special Features: | Radius End May Be Chamfered 25 Deg |
| Material: | Steel Comp 410 Overall Or Steel Comp 416 Overall |
| Material Document And Classification: | Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Astm A380 Assn Std Single Treatment Response Overall |

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-608> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.