

P/N MS16555-610

Military-Fasteners.com

#### Description

MS16555-610 Straight Headless Pin

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS16555610
Minimum Qty (MOQ):	100
NSN:	5315-00-947-7007
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



# P/N MS16555-610 Specifications

First End Style:	Chamfered
Second End Style:	Square
Pin Overall Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Pin Overall Diameter:	0.0782 Inches Minimum And 0.0784 Inches Maximum
First End Taper Length:	0.060 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	700 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall

## How to Order

Order this straight headless pin from our inventory online by visiting <u>https://military-fasteners.com/pins/straight+headless+pins/MS16555-610</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.