

Description

MS16555-611 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16555611
Minimum Qty (MOQ):	50
NSN:	5315-00-989-9230
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N MS16555-611 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Pin Overall Diameter:	0.0782 Inches Minimum And 0.0784 Inches Maximum
Second End Corner Radius:	0.008 Inches Minimum And 0.016 Inches Maximum
First End Taper Length:	0.068 Inches Minimum And 0.096 Inches Maximum
Features Provided:	Casehardened
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Shear Strength:	700 Double Pounds Per Square Inch
First End Taper Angle:	4.0 Degrees Minimum And 12.0 Degrees Maximum
Surface Finish:	125.0 Microinches Both Ends
Special Features:	Radius End May Be Chamfered 25 Deg
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-611> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.