

Description

MS16555-611 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS16555611 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5315-00-989-9230 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



NO IMAGE
AVAILABLE

P/N MS16555-611 Specifications

| | |
|--|---|
| First End Style: | Chamfered |
| Second End Style: | Radius |
| Pin Overall Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Pin Overall Diameter: | 0.0782 Inches Minimum And 0.0784 Inches Maximum |
| Second End Corner Radius: | 0.008 Inches Minimum And 0.016 Inches Maximum |
| First End Taper Length: | 0.068 Inches Minimum And 0.096 Inches Maximum |
| Features Provided: | Casehardened |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Shear Strength: | 700 Double Pounds Per Square Inch |
| First End Taper Angle: | 4.0 Degrees Minimum And 12.0 Degrees Maximum |
| Surface Finish: | 125.0 Microinches Both Ends |
| Special Features: | Radius End May Be Chamfered 25 Deg |
| Material: | Steel Comp 410 Overall Or Steel Comp 416 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-611> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.