

P/N MS16555-625

Description

steel, passivated, MS16555-625 Straight Headed Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS16555625

Minimum Qty (MOQ): 100

NSN: 5315-01-111-6812

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









P/N MS16555-625 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Pin Overall Diameter:	0.1251 Inches Minimum And 0.1253 Inches Maximum
Second End Corner Radius:	0.041 Inches Maximum
First End Taper Length:	0.065 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	1800 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Criticality Code Justification:	Zzzw And Feat
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Certified Free From Mercury Contamination, small Chamfer End May Be 0.016 In. Min 0.041 In. Max Radius In Lieu Of Chamfer
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Special Test Features:	Special Quality Control Testing
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Test Data Document:	81349-mil-p-23199 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Departure From Cited Document:	As Modified By Material Which Must Conform To Ships Parts Control Center Special Quality Control Provisions

How to Order

