

Description

MS16555-647 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16555647
Minimum Qty (MOQ):	25
NSN:	5315-00-809-1442
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16555-647 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Pin Overall Diameter:	0.2501 Inches Minimum And 0.2503 Inches Maximum
Second End Corner Radius:	0.031 Inches Minimum And 0.083 Inches Maximum
First End Taper Length:	0.162 Inches Nominal
Features Provided:	Casehardened
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	7200 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Radius End May Be Chamfered 25 Deg
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-647> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.