

Description

MS16555-654 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16555654
Minimum Qty (MOQ):	10
NSN:	5315-00-939-1144
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16555-654 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Pin Overall Diameter:	0.3126 Inches Minimum And 0.3128 Inches Maximum
Second End Corner Radius:	0.039 Inches Minimum And 0.104 Inches Maximum
First End Taper Length:	0.281 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	11000 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Radius End May Be Chamfered 20.0 To 30.0 Deg
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16555-654> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.