

Description

MS16556 series pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS16556620 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5315-00-060-4350 |
| ECCN: | EAR99 |
| National Motor Freight: | 105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes |



* See page 2 for technical characteristics

P/N MS16556-620 Specifications

| | |
|---|---|
| First End Style: | Chamfered |
| Second End Style: | Square |
| Pin Overall Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Pin Overall Diameter: | 0.0946 Inches Minimum And 0.0948 Inches Maximum |
| First End Taper Length: | 0.125 Inches Nominal |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| Shear Strength: | 1000 Double Pound |
| First End Taper Angle: | 4.0 Degrees Minimum And 16.0 Degrees Maximum |
| Surface Finish: | 16.0 Microinches Outside Diameter |
| Material: | Steel Comp 410 Overall Or Steel Comp 416 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16556-620> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.