

P/N MS16556-621

Description

MS16556-621 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS16556621

Minimum Qty (MOQ): 100

NSN: 5315-00-082-4858

ECCN: EAR99

National Motor Freight: 133300, Machinery / Machines Noi



^{*} See page 2 for technical characteristics

P/N MS16556-621 Specifications

First End Style:	Chamfered
Second End Style:	Square
Pin Overall Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Pin Overall Diameter:	0.0946 Inches Minimum And 0.0948 Inches Maximum
First End Taper Length:	0.134 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	1000 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Fed Std 66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this straight headless pin from our inventory online by visiting https://military-fasteners.com/pins/straight+headless+pins/MS16556-621 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/straight+headless+pins/MS16556-621 and selecting the