

P/N MS16556-621

Description

MS16556-621 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS16556621

Minimum Qty (MOQ): 100

NSN: 5315-00-082-4858

ECCN: EAR99

National Motor Freight: 133300, Machinery / Machines Noi



^{*} See page 2 for technical characteristics

P/N MS16556-621 Specifications

| First End Style: | Chamfered |
|--|---|
| Second End Style: | Square |
| Pin Overall Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Pin Overall Diameter: | 0.0946 Inches Minimum And 0.0948 Inches Maximum |
| First End Taper Length: | 0.134 Inches Nominal |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| Shear Strength: | 1000 Double Pound |
| First End Taper Angle: | 4.0 Degrees Minimum And 16.0 Degrees Maximum |
| Surface Finish: | 16.0 Microinches Outside Diameter |
| Material: | Steel Comp 410 Overall Or Steel Comp 416 Overall |
| Material Document And Classification: | Fed Std 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this straight headless pin from our inventory online by visiting https://military-fasteners.com/pins/straight+headless+pins/MS16556-621 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/straight+headless+pins/MS16556-621 and selecting the