

Description

MS16556-640 Straight Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16556640
Minimum Qty (MOQ):	50
NSN:	5315-00-968-3509
ECCN:	EAR99
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



* See page 2 for technical characteristics

P/N MS16556-640 Specifications

First End Style:	Chamfered
Second End Style:	Radius
Pin Overall Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Pin Overall Diameter:	0.1884 Inches Minimum And 0.1886 Inches Maximum
Second End Corner Radius:	0.062 Inches Maximum
First End Taper Length:	0.114 Inches Nominal
Second End Relationship With First End:	Not Identical
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Shear Strength:	4000 Double Pound
First End Taper Angle:	4.0 Degrees Minimum And 16.0 Degrees Maximum
Surface Finish:	16.0 Microinches Outside Diameter
Special Features:	Radius End May Be Chamfered 25 Deg
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16556-640> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.