

Description

MS16556-824 Straight Headless Pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16556824
Minimum Qty (MOQ):	50
NSN:	5315-01-592-6351
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS16556-824 Specifications

<b>First End Style:</b>	Chamfered
<b>Second End Style:</b>	Radius
<b>Pin Overall Length:</b>	1.000 Inches Nominal
<b>Pin Overall Diameter:</b>	0.0947 Inches Minimum And 0.0949 Inches Maximum
<b>First End Taper Length:</b>	0.906 Inches Nominal
<b>Second End Relationship With First End:</b>	Not Identical
<b>Hardness Rating:</b>	47.0 Rockwell C Minimum Inner Pin And 58.0 Rockwell C Maximum Inner Pin
<b>Hardness Rating:</b>	60.0 Rockwell C Nominal Overall
<b>Shear Strength:</b>	1000 Double Pounds Per Square Inch
<b>First End Taper Angle:</b>	4.0 Degrees Minimum And 16.0 Degrees Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/MS16556-824> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.