

# P/N MS16562-127

## **Description**

MS16562-127 Spring Pin

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS16562127
Minimum Qty (MOQ):	100
NSN:	5315-00-058-6079
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16562-127 Specifications

Overall Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.131 Inches Minimum And 0.135 Inches Maximum
Material Thickness:	0.028 Inches Minimum
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	2100 Double Pound
Material:	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Phosphate Zinc Overall
Surface Treatment Document And Classification:	Dod-p-16232,cl2 National Spec Single Treatment Response Overall
Style Designator:	Slotted

### **How to Order**

Order this spring pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/spring+pins/MS16562-127">https://military-fasteners.com/pins/spring+pins/MS16562-127</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.