

**Description**

length: 1/2", diameter: 5/64", tubular slotted, carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1656215
Minimum Qty (MOQ):	100
NSN:	5315-00-844-3953
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N MS16562-15 Specifications

<b>Overall Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Diameter:</b>	0.083 Inches Minimum And 0.086 Inches Maximum
<b>Material Thickness:</b>	0.018 Inches Minimum
<b>Hardness Rating:</b>	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	1300 Double Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66,comp 1070 Thru 1095 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.