

Description

length: 1/2", diameter: 5/64", tubular slotted, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1656215
Minimum Qty (MOQ):	100
NSN:	5315-00-844-3953
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS16562-15 Specifications

Overall Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.083 Inches Minimum And 0.086 Inches Maximum
Material Thickness:	0.018 Inches Minimum
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	1300 Double Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	66,comp 1070 Thru 1095 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.