

Description

MS16562-157 Spring Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS16562157 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5315-00-828-8520 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N MS16562-157 Specifications

| | |
|---|---|
| Overall Length: | 2.475 Inches Minimum And 2.525 Inches Maximum |
| Diameter: | 0.321 Inches Minimum And 0.328 Inches Maximum |
| Material Thickness: | 0.062 Inches Nominal |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Shear Strength: | 11500 Double Pound |
| Material: | Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Carbon Overall |
| Surface Treatment Document And Classification: | Dod-p-16232,c12 National Spec Single Treatment Response Overall |
| Style Designator: | Slotted |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-157> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.