

## P/N MS16562-190

### **Description**

length: 1/4", diameter: 1/16", tubular slotted, corrosion resistant steel, MS16562 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS16562190

Minimum Qty (MOQ): 50

NSN: 5315-00-847-3735

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16562-190 Specifications

Overall Length:	0.235 Inches Minimum And 0.265 Inches Maximum
Diameter:	0.066 Inches Minimum And 0.069 Inches Maximum
Material Thickness:	0.012 Inches Nominal
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

## **How to Order**

Order this spring pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/spring+pins/MS16562-190">https://military-fasteners.com/pins/spring+pins/MS16562-190</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.