



★ FASTENERS

Military-Fasteners.com

P/N MS16562-2

Description

length: 1/4", diameter: 1/16", tubular slotted, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS165622
Minimum Qty (MOQ):	50
NSN:	5315-00-844-3939
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N MS16562-2 Specifications

Overall Length:	0.235 Inches Minimum And 0.265 Inches Maximum
Diameter:	0.066 Inches Minimum And 0.069 Inches Maximum
Material Thickness:	0.012 Inches Minimum
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	850 Double Pounds Per Square Inch
Material:	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1075 Overall Or Steel Comp 1078 Overall Or Steel Comp 1080 Overall Or Steel Comp 1084 Overall Or Steel Comp 1085 Overall Or Steel Comp 1086 Overall Or Steel Comp 1090 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66,comp 1070 Thru 1095 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.