

Description

length: 1/2, diameter: 3/32", tubular, slotted, corrosion resistant steel, MS16562 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16562213
Minimum Qty (MOQ):	50
NSN:	5315-00-058-9731
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS16562-213 Specifications

Overall Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.099 Inches Minimum And 0.103 Inches Maximum
Material Thickness:	0.022 Inches Nominal
End Item Identification:	W/s: Systems, Jp-5 Aviation Fuels; Guided Missile Launching System, Mk 26 (gmls); Radar Set, An/pps-5b; Missile, Air Intercept, Sidewinder (aim-9); Traffic Jam, An/tlq-17a; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Test Consoles, Mini-sace; Missile, Air-to-air, Sparrow (aim-7)
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Shear Strength:	1000 Double Pound
Surface Finish:	80.0 Microinches Outside Diameter
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-213> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.