

## Description

length: 7/8", diameter: 3/32", tubular slotted, corrosion resistant steel, MS16562 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS16562217
Minimum Qty (MOQ):	50
NSN:	5315-00-058-9737
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



## P/N MS16562-217 Specifications

<b>Overall Length:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Diameter:</b>	0.094 Inches Nominal
<b>Material Thickness:</b>	0.022 Inches Nominal
<b>Hardness Rating:</b>	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	1000 Double Pounds Per Square Inch
<b>Surface Finish:</b>	80.0 Microinches Outside Diameter
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 420 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Astm A380 Assn Std Single Treatment Response Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-217> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.