

## Description


length: 1/2", diameter: 1/8", tubular slotted, corrosion resistant steel, MS16562 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS16562221
Minimum Qty (MOQ):	50
NSN:	5315-00-881-2253
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron



\* See page 2 for technical characteristics

## P/N MS16562-221 Specifications

<b>Overall Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Diameter:</b>	0.131 Inches Minimum And 0.135 Inches Maximum
<b>Material Thickness:</b>	0.028 Inches Nominal
<b>Hardness Rating:</b>	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 420 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-221> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.