

Description

MS16562-227 Spring Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS16562227 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5315-00-058-9756 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



NO IMAGE
AVAILABLE

P/N MS16562-227 Specifications

| | |
|---|---|
| Overall Length: | 1.230 Inches Minimum And 1.270 Inches Maximum |
| Diameter: | 0.131 Inches Minimum And 0.135 Inches Maximum |
| Material Thickness: | 0.028 Inches Nominal |
| Hardness Rating: | 43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall |
| Shear Strength: | 2100 Double Pound |
| Material: | Steel Comp 410 Overall Or Steel Comp 420 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Astm A380 Assn Std Single Treatment Response Overall |
| Style Designator: | Slotted |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-227> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.