

**Description**

MS16562-231 Spring Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16562231
Minimum Qty (MOQ):	5
NSN:	5315-00-058-9767
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16562-231 Specifications

<b>Overall Length:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Diameter:</b>	0.162 Inches Minimum And 0.167 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>End Item Identification:</b>	W/s:helicopter, Advance Attack, Ah-1w; Mortar, 60mm, M224; Aircraft, C-2a (reprocured); Aircraft, Eagle F-15; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Search And Rescue, Hh-60h; Aircraft, Airlifter C-17a; Mk 28, 5-inch 38 Caliber Twin Gun Mount; Fire Control System, Missile Mk 74 (fcs); Helicopter, Mh-53e
<b>Hardness Rating:</b>	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	3000 Double Pound
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 420 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Astm A380 Assn Std Single Treatment Response Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/pin/MS16562-231> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.