

Description

Steel comp, MS16562 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16562236
Minimum Qty (MOQ):	25
NSN:	5315-00-058-9782
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS16562-236 Specifications

Overall Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Diameter:	0.194 Inches Minimum And 0.199 Inches Maximum
Material Thickness:	0.040 Inches Nominal
End Item Identification:	Mrap Rg-33
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Shear Strength:	4400 Double Pound
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-236> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.