

**Description**

MS16562-239 Spring Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | MS16562239                  |
| Minimum Qty (MOQ):      | 25                          |
| NSN:                    | 5315-00-587-2705            |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



NO IMAGE  
AVAILABLE

## P/N MS16562-239 Specifications

|   |   |
|---|---|
| <b>Overall Length:</b>                                | 1.230 Inches Minimum And 1.270 Inches Maximum                       |
| <b>Diameter:</b>                                      | 0.194 Inches Minimum And 0.199 Inches Maximum                       |
| <b>Material Thickness:</b>                            | 0.040 Inches Nominal  |
| <b>Hardness Rating:</b>                               | 43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall |
| <b>Shear Strength:</b>                                | 4400 Double Pound   |
| <b>Material:</b>                                      | Steel Comp 410 Overall Or Steel Comp 420 Overall                    |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall                           |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Astm A380 Assn Std Single Treatment Response Overall                |
| <b>Style Designator:</b>                              | Slotted   |

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-239> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.