



★ FASTENERS

Military-Fasteners.com

P/N MS16562-240

Description

length: 1-1/2", diameter: 15/64", tubular slotted, corrosion resistant steel, MS16562 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16562240
Minimum Qty (MOQ):	25
NSN:	5315-00-200-3183
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16562-240 Specifications

Overall Length:	1.480 Inches Minimum And 1.520 Inches Maximum
Diameter:	0.188 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-240> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.